

Job Name:	Location:
Purchaser:	
Engineer:	
Submitted To:	For: <input type="checkbox"/> Reference <input type="checkbox"/> Approval <input type="checkbox"/> Construction
Submitted By:	Date:
Unit Designation: Schedule #:	Model No.:

Capacities:

Cooling	36,000 Btu/h
Heating	40,000 Btu/h

Cooling Mode Nominal Conditions:

Indoor: 80°F DB / 67°F WB
Outdoor: 95°F DB
Pipe Length: 25 ft
Level Difference: 0 ft

Heating Mode Nominal Conditions:

Indoor: 70°F DB
Outdoor: 47°F DB / 43°F WB
Pipe Length: 25 ft
Level Difference: 0 ft

Fan:

Fan Type	Sirocco Fan
Fan Motor Output	130 Watts
Airflow Rate (H/L)	830/670 cfm
Drive	Direct Drive

Power Supply:

V/PH/Hz	208-230/1/60
Minimum Circuit Amps (MCA)	1.4 Amps
Nominal Power Input – Cooling	161 Watts
Nominal Power Input - Heating	161 Watts
Maximum Fuse Amps (MFA)	15 Amps
Full Load Amps (FLA)	1.1 Amps

Refrigerant & Piping:

Refrigerant	R-410A
Control	Electronic Expansion Valve
Liquid Refrigerant Piping	φ3/8" Flare
Gas Refrigerant Piping	φ5/8" Flare
Condensate Drain Piping (OD)	φ1"

Unit Data:

Sound Pressure Level (H/L)	
- measured at 3ft at and below the unit	46/41 dBA
Weight	90 lbs

Standard Features:

- One year limited labor warranty
- One year parts warranty
- Washable front grille
- Long life filter

Options:

- Wired remote controller
- Wireless remote controller
- Simplified controller

