



## Innovative. Efficient. Durable.

In every Daikin commercial heat pump system, our high-performance, high-efficiency compressors operate in tandem with our high-efficiency coil design. This innovative system offers one of the best levels of reliability, durability and efficiency we offer in our commercial packaged heat pumps. The Daikin DZ14 and DZ11 commercial heat pumps feature a powder-paint finish over heavy-gauge galvanized steel. This provides premium durability and improved UV protection. The attractive louvered metal guard protects the coil from damage and strengthens the unit. The base pan is elevated to provide excellent water drainage and helps keep the coil away from debris that can collect inside the unit.

- » Designed for ground-level or rooftop mount
- » An energy-efficient compressor with an internal relief valve
- » A louvered cabinet made of heavy-gauge galvanized steel that protects the coil
- » A factory-installed in-line filter drier
- » Brass liquid and suction line service valves
- » A high-efficiency condenser coil made of corrugated aluminum fins and rifled refrigeration-grade copper tubing
- » Refrigerant accumulator

### DZ14 Unit Features

- » Energy efficient compressor
- » Quiet operating top discharge
- » High-efficiency copper tube / aluminum fin coil
- » Brass liquid and suction service valves
- » High- and low-pressure switches
- » Factory-installed filter drier
- » Units meet the performance outlined in Table 6.8.1-2 of ASHRAE Standard 90.1-2016
- » AHRI Certified; ETL Listed



### OUTSTANDING WARRANTY\* PROTECTION



\* Complete warranty details available from your local distributor or manufacturer's representative or at [www.daikincomfort.com](http://www.daikincomfort.com).

### DZ14 Cabinet Features

- » Innovative sound control top design
- » Steel louver coil guard protects the coil from damage and adds strength to unit
- » Bottom pan rails elevate unit above slab
- » Heavy-gauge galvanized-steel cabinet
- » Attractive Nickel Gray powder-paint finish
- » When properly anchored, meets the 2010 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)

## DZ11 Unit Features

- » Two-stage energy efficient compressor with internal pressure relief valve
- » High-capacity, steel-cased, bi-flow heat pump filter drier
- » Liquid refrigerant return protection
- » Check flowrate heating mode expansion device
- » Reliable, time-initiated, temperature-terminated defrost control
- » High and low pressure switches
- » Discharge line muffler
- » Brass liquid and suction line service valves mounted at a 90° angle with sweat connections and service ports
- » High-efficiency copper tube / aluminum fin coil
- » Units meet the performance outline in Table 6.8.1-2 of ASHRAE Standard 90.1-2016
- » AHRI Certified; ETL Listed

## DZ11 Cabinet Features

- » Innovative sound control top design
- » Steel louver coil guard protects coil from damage and adds strength to the unit
- » Heavy-gauge, galvanized-steel cabinet
- » Attractive Nickel Gray powder-paint finish
- » When properly anchored, meets the 2010 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available).

## DZ14 | DZ11 Heat Pumps | 3 Phase | DZ14: 14 SEER 3 - 5 Tons | DZ11: 11 EER / 13-13.5 IEER 7½ - 10-Tons

Model	Nominal Capacities (BTU/h)		SEER	Voltage-Phase	Dimensions			Service Valve		dB(A)	Ship Weight (lbs)
	Cooling	Heating			W"	D"	H"	Liquid"	Suction"		
DZ14SA0363**	34,600	32,800	14.0	208/230-3	29	29	32¼	¾	¾	74	232
DZ14SA0364**	34,600	32,800	14.0	460-3	29	29	32¼	¾	¾	74	231
DZ14SA0483**	45,000	44,500	14.0	208/230-3	29	29	34¼	¾	1½	76	235
DZ14SA0484**	45,000	44,500	14.0	460-3	29	29	34¼	¾	1½	76	234
DZ14SA0603**	56,500	59,000	14.0	208/230-3	35½	35½	34¼	¾	1½	75	262
DZ14SA0604**	56,500	59,000	14.0	460-3	35½	35½	34¼	¾	1½	75	261

Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

Model	Nominal Capacity (BTU/h)		EER	Voltage-Phase	Dimensions			Service Valve		dB(A)	Ship Weight (lbs)
	Cooling	Heating			W"	D"	H"	Liquid"	Suction"		
DZ11TA0903A	93,000	82,000	11	208/230-3	35½	35½	41½	¾	1¾	84	355
DZ11TA0904A	93,000	82,000	11	460-3	35½	35½	41½	¾	1¾	84	355
DZ11TA1203A	115,000	100,000	11	208/230-3	35½	35½	41½	¾	1¾	84	375
DZ11TA1204A	115,000	100,000	11	460-3	35½	35½	41½	¾	1¾	84	370

Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



### About Daikin:

Daikin Industries, Ltd. (DIL) is a global Fortune 1,000 company which celebrated its 90th anniversary in May 2014. The company is recognized as one of the largest HVAC (Heating, Ventilation Air Conditioning) manufacturers in the world. Daikin is primarily engaged in developing indoor comfort products and refrigeration systems for residential, commercial and industrial applications. Its consistent success is derived, in part, from a focus on innovative, energy-efficient and premium quality indoor climate and comfort management solutions.

Daikin and its design are trademarks owned by Daikin.



Our continuing commitment to quality products may mean a change in specifications without notice.

© 2018 **DAIKIN NORTH AMERICA LLC** · Houston, Texas · USA · [www.daikincomfort.com](http://www.daikincomfort.com) or [www.daikinac.com](http://www.daikinac.com)