


Job Name:	
Tag#	



Submittal Data Sheet

FTXG09HVJU / RXG09HVJU

0.75-Ton Wall Mounted Heat Pump System



Complete warranty details available from your local dealer or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. If product is installed in a commercial application, limited warranty period is 5 years.

Indoor Specifications

Airflow Rate (cfm)	Cooling		Heating	
	H	M	H	M
	420	325	438	346
	L		L	
	230		258	
Sound (dBA) H / M / L	42 / 33 / 26		42 / 35 / 28	
Dimensions (H × W × D) (in)		12 × 35-1/16 × 8-1/4		
Weight (Lbs)		31		

Outdoor Specifications

Compressor	Hermetically Sealed Swing Type			
Refrigerant	R-410A			
Factory Charge (Lbs)	3.1			
Refrigerant Oil	PVE (FVC50K)			
Airflow Rate (cfm)	Cooling		Heating	
	H	1,178	H	1,095
Sound Pressure Level (dBA)	46			
Dimensions (H × W × D) (in)	22-3/8 × 31-5/16 × 11-1/4			
Weight (Lbs)	99			

Efficiency

Cooling		Heating	
SEER	26.1	HSPF	11.0
EER	15.8	COP	4.51

Performance

Cooling (Btu/hr)	
Rated (Min/Max)	9,000 (5,300 / 12,300)
Sensible @ AHRI	8,900
Moisture Removal Pt/h	3.3
Operating Range	14°F – 109°F

Rated Cooling Conditions: Indoor: 80°F DB/67°F WB
Outdoor: 95°F DB/75°F WB

Heating (Btu/hr)	
1: @ 47° Rated (Min/Max)	12,000 (4,400 / 18,000)
2: @ 17° Rated	8,100
Operating Range	-4°F – 75°F

1: Rated Heating Conditions: Indoor: 70°F DB/60°F WB
Outdoor: 47°F DB/43°F WB
2: Rated Heating Conditions: Indoor: 70°F DB/60°F WB
Outdoor: 17°F DB/15°F WB

Electrical

	208/60/1	230/60/1
System MCA	14.5	14.5
System MFA	15	15
Compressor RLA	2.3	2.1
Outdoor fan motor FLA	.10	.10
Outdoor fan motor W	60	60
Indoor fan motor FLA	.13	.12
Indoor fan motor W	57	57

MFA: Max. fuse amps MCA: Min. circuit amps (A) FLA: Full load amps (A)
RLA: Rated load amps (A) W: Fan motor rated output (W)

Piping


Liquid (in)	1/4
Gas (in)	3/8
Drain (in)	11/16
Max. Interunit Piping Length (ft)	32
Max. Interunit Height Difference (ft)	26
Chargeless (ft)	-
Additional Charge of Refrigerant (oz/ft)	-

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Revision Date: September 2018


Page 1 of 4



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

RXG09HVJU Dimensional Data



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Optional Accessories



Indoor Unit

Included	Part Number	Description
	DACA-CP1-1	Inline Condensate Pump (Fits inside all Daikin wall & floor mount units)
	DACA-CP4-1	External Condensate Pump

Outdoor Unit

Included	Part Number	Description
	DACA-WB-3	Powder-Coated Wall-Mounted Bracket
	KKP937A4	Drain Plug for OD Unit
	KPW937C4	Air Adjustment Grille

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Revision Date: September 2018

Page 4 of 4