



## Submittal Data Sheet

3 Ton, Uncased Upflow/Downflow, Coil

CAUF3636B6

### STANDARD FEATURES

- All-Aluminum evaporator coil
- Optimized for use with R-410A refrigerant
- Some models suitable for use with R-410A or R-22 refrigerant
- CAPT models feature factory-installed thermal expansion valves for cooling and heat pump applications
- Check flowrator for cooling and heat pump applications
- Vertical and horizontal models available
- 21" depth for easier attic access
- Split seam front for easy access
- Foil-faced insulation covers the internal casing to reduce cabinet condensation
- Galvanized, leather grain-embossed finish
- Rust resistant, thermoplastic drain pans featuring a low water-retention design
- DecaBDE-free thermoplastic drain pan with secondary drain connections
- UV-resistant drain pan
- AHRI certified
- ETL listed





Submittal Data Sheet

3 Ton, Uncased Upflow/Downflow, Coil  
CAUF3636B6

| PERFORMANCE       |            |                                      |                                      |
|-------------------|------------|--------------------------------------|--------------------------------------|
| Product Model No. | CAUF3636B6 | Product Model Name:                  | 3 Ton, Uncased Upflow/Downflow, Coil |
| Type:             | Coil       | Cooling Capacity (Nominal) (Btu/hr): | 36,000                               |

| PRODUCT DETAILS          |                          |                                       |     |
|--------------------------|--------------------------|---------------------------------------|-----|
| Dimensions (HxWxD) (in): | 19-3/8 x 16-1/2 x 20-1/8 | Suction Valve Connection Size (inch): | 3/4 |
| Net Weight (lb):         | 25                       | Liquid Valve Connection Size (inch):  | 3/8 |
| Gross Weight (lb):       | 25                       | Condensate Connection (inch):         | 3/4 |

## Submittal Data Sheet

3 Ton, Uncased Upflow/Downflow, Coil

CAUF3636B6

## DIMENSIONAL DRAWING

| MODEL      | DIMENSIONS |      |     | NOMINAL<br>TONS | CONNECTION |         | PISTON<br>SIZE* | SHIP<br>WEIGHT<br>(LBS) |
|------------|------------|------|-----|-----------------|------------|---------|-----------------|-------------------------|
|            | W          | H    | A   |                 | LIQUID     | SUCTION |                 |                         |
| CAUF1824A6 | 13"        | 16¼" | 13" | 1½-2            | ⅜"         | ¾"      | .059            | 18                      |
| CAUF1824B6 | 16½"       | 16⅞" | 13" | 1½-2            | ⅜"         | ¾"      | .059            | 23                      |
| CAUF1824C6 | 20"        | 16⅞" | 17" | 1½-2            | ⅜"         | ¾"      | .059            | 27                      |
| CAUF3030A6 | 13"        | 20⅞" | 17" | 2½              | ⅜"         | ¾"      | .065            | 25                      |
| CAUF3030B6 | 16½"       | 18¾" | 17" | 2½              | ⅜"         | ¾"      | .065            | 22                      |
| CAUF3030C6 | 20"        | 17⅞" | 17" | 2½              | ⅜"         | ¾"      | .065            | 25                      |
| CAUF3030D6 | 23"        | 17⅞" | 17" | 2½              | ⅜"         | ¾"      | .065            | 32                      |
| CAUF3131B6 | 16½"       | 20⅞" | 17" | 2½              | ⅜"         | ¾"      | .068            | 27                      |
| CAUF3137B6 | 16½"       | 27"  | 25" | 2½-3            | ⅜"         | ¾"      | .071            | 53                      |
| CAUF3131C6 | 20"        | 20"  | 17" | 2½              | ⅜"         | ¾"      | .068            | 31                      |
| CAUF3636A6 | 13"        | 19½" | 17" | 3               | ⅜"         | ¾"      | .071            | 30                      |
| CAUF3636B6 | 16½"       | 19⅞" | 17" | 3               | ⅜"         | ¾"      | .071            | 25                      |
| CAUF3636C6 | 20"        | 19⅞" | 17" | 3               | ⅜"         | ¾"      | .071            | 28                      |
| CAUF3636D6 | 23"        | 19⅞" | 17" | 3               | ⅜"         | ¾"      | .071            | 36                      |
| CAUF3642C6 | 20"        | 19"  | 17" | 3-3½            | ⅜"         | ¾"      | .078            | 29                      |
| CAUF3642D6 | 23"        | 19⅞" | 17" | 3-3½            | ⅜"         | ¾"      | .078            | 34                      |
| CAUF3743C6 | 20"        | 28⅞" | 25" | 3-3½            | ⅜"         | ⅞"      | .078            | 46                      |
| CAUF3743D6 | 23"        | 27⅞" | 25" | 3-3½            | ⅜"         | ⅞"      | .078            | 43                      |
| CAUF4860C6 | 20"        | 28"  | 25" | 4-5             | ⅜"         | ⅞"      | .093            | 48                      |
| CAUF4860D6 | 23"        | 28"  | 25" | 4-5             | ⅜"         | ⅞"      | .093            | 39                      |
| CAUF4961C6 | 20"        | 28"  | 25" | 4-5             | ⅜"         | ⅞"      | .093            | 54                      |
| CAUF4961D6 | 23"        | 27"  | 25" | 4-5             | ⅜"         | ⅞"      | .093            | 59                      |

\* Shipped with Coil

Note: For a properly matched system and piston sizing information, refer to Daikin piston kit chart of the corresponding Daikin outdoor unit.

## DIMENSIONS

