



Submittal Data Sheet

26 TON, 230V, VRV IV HP

RXYQ312TATJU

FEATURES

- Larger capacity single modules ranging up to 14 tons and systems up to 34 tons allow for a more flexible system design
- Variable Refrigerant Temperature (VRT) control allows the VRV IV to deliver up to 28% of improvement in seasonal cooling efficiency compared to previous Daikin VRV heat pump systems
- Modular and lightweight enables flexibility in system layout and installation with larger capacity single modules reducing electrical, piping connections
- System wide auto-climate adjustment technology to increase the energy efficiency
- Improved efficiency with IEER values now up to 28
- The rated seasonal cooling efficiency has been improved by an average of 11%
- All inverter compressors to increase the efficiency and avoid starting current inrush
- Same product structure for 230V and 460V simplifies ordering
- New configurator software designed to simplify the commissioning and maintenance of the system
- Factory standard coil guards
- Assembled in the US to increase flexibility and reduce lead times
- Standard Limited Warranty: 10-year limited parts warranty



VRV IV



BENEFITS

- Can operate up to 54 indoor units on a single piping network
- Modular and lightweight - enables flexibility in system layout and installation
- Refrigerant cooled inverted technology to avoid influence from ambient temperatures
- Integrated inverter technology deliver maximum efficiency during part load conditions and provide precise individual zone control
- Heat exchanger coil wraps around on all 4 sides of the unit to increase the surface area and efficiency
- 3 row 7mm heat exchanger coil improves efficiency
- Corrosion resistance 1000hr salt spray tested Daikin PE blue fin heat exchanger
- Design flexibility with long piping lengths up to 3,280 ft. total and 100 ft. vertical separation between indoor units
- Designed with reduced MOP to optimize installation cost
- Digital display on the unit for improved and faster configuration, commissioning, and trouble shooting



Submittal Data Sheet

26 TON, 230V, VRV IV HP

RXYQ312TATJU

PERFORMANCE

Outdoor Unit Model No.	RXYQ312TATJU	Outdoor Unit Name:	26 TON, 230V, VRV IV HP
Type:	Heat Pump	Unit Combination:	RXYQ144TATJU + RXYQ168TATJU
Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Rated Piping Length(ft):			
Rated Height Difference (ft):			
Rated Cooling Capacity (Btu/hr):	296,000	Rated Heating Capacity (Btu/hr):	334,000
Nom Cooling Capacity (Btu/hr):	312,000	Nom Heating Capacity (Btu/hr):	351,000
Cooling Input Power (kW):	33.10	Heating Input Power (kW):	24.70
EER (Non-Ducted/Ducted):	9.80 / 9.60	Heating COP (Non-Ducted/Ducted):	3.3 / 3.2
IEER (Non-Ducted/Ducted):	19.90 / 18.80	Heating COP 17F (Non-Ducted/Ducted):	2.3 / 2.2

OUTDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 3	Compressor Stage:	Inverter
Power Supply Connections:	L1, L2, L3 Ground	Capacity Control Range (%):	10 - 100
Min. Circuit Amps MCA (A):	55.1+55.1	Capacity Index Limit:	156.0 - 405.0
Max Overcurrent Protection (MOP) (A):	60+60	Airflow Rate (H) (CFM):	8228+8228
Max Starting Current MSC(A):		Gas Pipe Connection (inch):	1-3/8
Rated Load Amps RLA(A):	(16.7+16.7)+(18.8+18.8)	Liquid Pipe Connection (inch):	3/4
Dimensions (Height) (in):	66-11/16	H/L Pressure Connection (inch)	
Dimensions (Width) (in):	48-7/8+48-7/8	H/L Equalizing Connection (inch)	
Dimensions (Depth) (in):	30-3/16	Sound Pressure (H) (dBA):	68
Net Weight (lb):	695+695	Sound Power Level (dBA):	
		Max. No. of Indoor Units:	54

Submittal Data Sheet 26 TON, 230V, VRV IV HP RXYQ312TATJU

SYSTEM DETAILS			
Refrigerant Type:	R-410A	Cooling Operation Range (°F DB):	23 - 122
Holding Refrigerant Charge (lbs):	18.1+17.2	Heating Operation Range (°F WB):	-4 - 60
Additional Charge (lb/ft):		Max. Pipe Length (Vertical) (ft):	295
Pre-charge Piping (Length) (ft):		Cooling Range w/Baffle (°F DB):	-
Max. Pipe Length (Total) (ft):	540	Heating Range w/Baffle (°F WB):	-
Max Height Separation (Ind to Ind ft):			

DIMENSIONAL DRAWING

