



Submittal Data Sheet

6 Ton, 230V VRV IV HP

RXYQ72TATJU

FEATURES

- Larger capacity single modules ranging up to 14 tons and systems up to 34 tons allow for a more flexible system design
- Variable Refrigerant Temperature (VRT) control allows the VRV IV to deliver up to 28% of improvement in seasonal cooling efficiency compared to previous Daikin VRV heat pump systems
- Modular and lightweight enables flexibility in system layout and installation with larger capacity single modules reducing electrical, piping connections
- System wide auto-climate adjustment technology to increase the energy efficiency
- Improved efficiency with IEER values now up to 28
- The rated seasonal cooling efficiency has been improved by an average of 11%
- All inverter compressors to increase the efficiency and avoid starting current inrush
- Same product structure for 230V and 460V simplifies ordering
- New configurator software designed to simplify the commissioning and maintenance of the system
- Factory standard coil guards
- Assembled in the US to increase flexibility and reduce lead times
- Standard Limited Warranty: 10-year limited parts warranty



BENEFITS

- Can operate up to 12 indoor units on a single piping network
- Modular and lightweight - enables flexibility in system layout and installation
- Refrigerant cooled inverted technology to avoid influence from ambient temperatures
- Integrated inverter technology deliver maximum efficiency during part load conditions and provide precise individual zone control
- Heat exchanger coil wraps around on all 4 sides of the unit to increase the surface area and efficiency
- Corrosion resistance 1000hr salt spray tested Daikin PE blue fin heat exchanger
- Design flexibility with long piping lengths up to 3,280 ft. total and 100 ft. vertical separation between indoor units
- Designed with reduced MOP to optimize installation cost
- Digital display on the unit for improved and faster configuration, commissioning, and trouble shooting



VRV IV





Submittal Data Sheet

6 Ton, 230V VRV IV HP

RXYQ72TATJU

PERFORMANCE

Outdoor Unit Model No.	RXYQ72TATJU	Outdoor Unit Name:	6 Ton, 230V VRV IV HP
Type:	Heat Pump	Unit Combination:	
Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Rated Piping Length(ft):			
Rated Height Difference (ft):			
Rated Cooling Capacity (Btu/hr):	69,000	Rated Heating Capacity (Btu/hr):	73,000
Nom Cooling Capacity (Btu/hr):	72,000	Nom Heating Capacity (Btu/hr):	81,000
Cooling Input Power (kW):	4.62	Heating Input Power (kW):	5.46
EER (Non-Ducted/Ducted):	14.70 / 12.70	Heating COP (Non-Ducted/Ducted):	3.7 / 3.3
IEER (Non-Ducted/Ducted):	25.80 / 20.70	Heating COP 17F (Non-Ducted/Ducted):	2.4 / 2.3

OUTDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 3	Compressor Stage:	Inverter
Power Supply Connections:	L1, L2, L3 Ground	Capacity Control Range (%):	20 - 100
Min. Circuit Amps MCA (A):	27.6	Capacity Index Limit:	36.0 - 93.0
Max Overcurrent Protection (MOP) (A):	35	Airflow Rate (H) (CFM):	5544
Max Starting Current MSC(A):		Gas Pipe Connection (inch):	3/4
Rated Load Amps RLA(A):	15.7	Liquid Pipe Connection (inch):	3/8
Dimensions (Height) (in):	66-11/16	H/L Pressure Connection (inch)	
Dimensions (Width) (in):	36-11/16	H/L Equalizing Connection (inch)	
Dimensions (Depth) (in):	30-3/16	Sound Pressure (H) (dBA):	58
Net Weight (lb):	435	Sound Power Level (dBA):	78
		Max. No. of Indoor Units:	12

Submittal Data Sheet

6 Ton, 230V VRV IV HP

RXYQ72TATJU

SYSTEM DETAILS

Refrigerant Type:	R-410A	Cooling Operation Range (°F DB):	23 - 122
Holding Refrigerant Charge (lbs):	13	Heating Operation Range (°F WB):	-4 - 6
Additional Charge (lb/ft):		Max. Pipe Length (Vertical) (ft):	295
Pre-charge Piping (Length) (ft):		Cooling Range w/Baffle (°F DB):	-
Max. Pipe Length (Total) (ft):	540	Heating Range w/Baffle (°F WB):	-
Max Height Separation (Ind to Ind ft):			

DIMENSIONAL DRAWING

